# **HEMEL<sup>®</sup> Fiber Cement Primer**

Description: Water-based fiber cement primer that allows board to breathe

Color: Cream

Gloss: Matt

Type: Water-based

# **General Features:**

- High hiding power
- Allows board to breathe
- Elastic
- Alkali resistant
- Lead-free
- Environmentally friendly
- Ready to use

Packaging Size: 2,5 L., 15 L.

## Where To Use:

• Fiber cement boards

# Product Data:

Solid Content (% weight):	60,97 ± 1
Viscosity (DIN6, 20°C):	23" ± 2
Density (g/cm <sup>3</sup> ):	1,45 ± 0,02
VOC (g/L):	26
Application Method:	Brush or roller
Shelf Life (5-35°C):	1 year for unopened can
Number of Coats:	1 coat
Coverage (m²/L):	10 m <sup>2</sup> depending on board type
Drying Time (at 20°C and 40-65% relative humidity):	Touch Dry: 30 minutes Complete Dry: 2 hours
Thinning:	Ready to use, does not require thinning. (At very high temperatures 10% drinking water may be added).



#### **Surface Preparation:**

- Remove any dirt, oil and dust from the surface.
- Sand the surface with sandpaper #150/180.
- Thoroughly clean the generated dust.

# Application:

- The product is ready to use and does not require thinning. (At very high temperatures 10% drinking water may be added).
- Stir the product thoroughly before use and check its homogeneity. Repeat this process during the application.
- Apply the product in 1 coat by a brush or roller.
- Wait 2 hours for complete dry.
- Perform a slight sanding with sandpaper #180/220. Thoroughly clean the generated dust and apply HEMEL Fiber Cement Paint-Translucent or HEMEL Fiber Cement Paint-Opaque.

#### Instructions:

- FOR EXTERIOR USE ONLY.
- Keep product closed when not in use.
- The general application temperature of the product is between 15°C to 25°C at a relative humidity range of 40-65%.
- Do not apply the product under direct sunlight or rain.
- The product should be protected from freezing and stored at temperatures between 5°C to 35°C.
- Painting tools should be cleaned with soap and plenty of warm water after application.

#### Safety Precautions:

- USE WITH ADEQUATE VENTILATION.
- KEEP OUT OF REACH OF CHILDREN.
- Do not transfer contents to other containers for storage.
- Do not use empty cans for other purposes.
- To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying.
- Avoid contact with eyes and skin.
- Wash hands after using.
- FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.
- Dispose of contents/cans in accordance with national regulations.
- Please refer to the Safety Data Sheet (SDS) of the product for health and safety information.

#### **Certificates:**

EN71-3 Toy Safety Certificate